## .308 Win. SWISS P Ball

## 11.4 g/176 gr

Match grade accuracy

Coordinated ballistics with SWISS P Target, Styx Action, Armour Piercing and Tactical rounds up to 100 m

Militarised and optimised for automatic weapons

Full metal jacket bullet design















Cartridge	7.62×51/.308 Win.	
Projectile	FMJ, 11.4g/176gr	
Projectile material	tombac jacket, lead core	
Ballistic coefficient G1	0.5225 (ICAO)	
Primer	SINOXID	
Case material	CuZn – alloy	
Cartridge weight	25.4g	
Performance		
Term of reference	C.I.P.	
Mean chamber pressure	max. 4 150 bar	(21 °C)
Temperature range	–54°C to +52°C	
Mean muzzle velocity	790 +20/-12 m/s (2 592 +66/-39 fps)	650 mm barrel
Mean muzzle energy (Min–Max)	3 557 J (3 450-3 740 J)	
Accuracy at 300 m	S <sub>a</sub> ≤ 32 mm	
Packaging		
Standard cardboard box	20rds/cardboard box, 200rds/cardboard box, 10000rds EU pallet	
Military M2A1 metal box	10rds/cardboard box, 400rds/M2A1 metal box, 24000rds EU pallet	



