

.338 Lapua Mag. SWISS P Ball

16.3 g / 251 gr

Match grade accuracy

Minimised muzzle flash for better concealment of the shooter

Temperature independent propellant guarantees a consistent point of impact

Coordinated ballistics with SWISS P Target, Styx Action, Armour Piercing and Tactical rounds up to 300 m

Also available as L916



| Cartridge | 8.6×70 / .338 Lapua Mag. | |
|------------------------------|---|---------------|
| Projectile | FMJ, 16.3 g/251 gr | |
| Projectile material | tombac jacket, lead core | |
| Ballistic coefficient G1 | 0.6571 (ICAO) | |
| Primer | SINOXID | |
| Case material | CuZn – alloy | |
| Cartridge weight | 44.5 g | |
| Performance | | |
| Term of reference | C.I.P. | |
| Mean chamber pressure | max. 4 200 bar | (21 °C) |
| Mean muzzle velocity | 855 ± 15 m/s (2 805 ± 49 fps) | 650 mm barrel |
| Mean muzzle energy (Min–Max) | 5 958 J (5 751 – 6 169 J) | |
| Accuracy at 300 m | $S_a \leq 25.5$ mm | |
| Packaging | | |
| Military M2A1 metal box | 10rds / cardboard box, 200rds / M2A1 metal box, 16 000rds EU pallet | |

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products. All information and specifications shown in factsheets are non-binding and subject to alterations without prior notice at any time. 01.2023

SwissP Defence AG | info@swiss-p.com | www.swiss-p.com

SWISS 
The Sniper's Choice