

.338 Lapua Mag. SWISS P Styx Action

16.0 g/247 gr

Outstanding stopping power while reducing the risk of collateral damage

Match grade accuracy

Temperature independent propellant guarantees a consistent point of impact

Coordinated ballistics with SWISS P Ball, Target, Armour Piercing and Tactical rounds up to 300 m



Cartridge	8.6×70 / .338 Lapua Mag.	
Projectile	JHP, 16.0 g/247 gr	
Projectile material	tombac jacket, lead core	
Ballistic coefficient G1	0.4328 (ICAO)	
Primer	SINOXID	
Case material	CuZn – alloy	
Cartridge weight	44.2 g	
Performance		
Term of reference	C.I.P.	
Mean chamber pressure	max. 4200 bar	(21 °C)
Mean muzzle velocity	875 ± 15 m/s (2871 ± 49 fps)	650 mm barrel
Mean muzzle energy (Min–Max)	6 125 J (5917–6337 J)	
Accuracy at 300 m	$S_a \leq 27.5$ mm	
Packaging		
Military M2A1 metal box	10rds / cardboard box, 200rds / M2A1 metal box, 16 000rds NATO pallet	

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products. All information and specifications shown in factsheets are non-binding and subject to alterations without prior notice at any time. 01.2023

SwissP Defence AG | info@swiss-p.com | www.swiss-p.com

SWISS 
The Sniper's Choice